


TAMC640 Virtex-5 AMC with FMC Slot



Application Information

The TAMC640 is a standard single Mid-Size or Full-Size AMC module providing a user configurable Virtex-5 FPGA. The integrated PCIe Endpoint Block of the Virtex-5 can be used to build an x1, x4 or x8 PCIe link via AMC Port 4-11. The implementation of other protocols like SRIO or XAUI is also possible. AMC Ports 0 & 1, commonly used for Gigabit Ethernet, are also connected to the FPGA. The integrated Gigabit Ethernet MACs of the Virtex-5 allow fast and easy protocol implementation.

To allow direct board-to-board communication, AMC Ports 12-17 are connected to Virtex-5 I/Os, allowing AC-coupled LVDS communication with a port speed up to 1.0Gb/sec.

For flexible I/O solutions the TAMC640 provides a VITA 57.1 high pin count FMC Module slot, allowing active and passive signal conditioning. All FMC I/O lines are directly connected to the FPGA, which maintains the flexibility of the Select I/O technology of the Virtex-5 FPGA.

In addition, the FPGA is connected to the following external memories:

- two banks of DDR2 DRAM (up to 128 M x 16 (256 MB) each)
- one bank of QDR-II SRAM (up to 4 M x 18 (8 MB))

Multiple clocks from the AMC-interface, the FMC and from on-board sources are supplied to the FPGA.

The FPGA is configured by a flash device, which is in-system programmable and able to store multiple code versions.

The TAMC640 supports encrypted FPGA bitstream usage. Encrypted FPGA bitstreams cannot be copied or reverse engineered, securing your intellectual property.

The IPMI Connectivity Records located inside the Module Management Controller (MMC) can be modified by the

customer (e.g. via IPMI), to adapt to the different possible communication protocols (PCIe, SRIO, XAUI, ...).

User applications for the TAMC640 require the full ISE Foundation software, which must be purchased from Xilinx.

The Engineering Documentation TAMC640-ED includes all information needed for customer specific FPGA programming. The FPGA Development Kit TAMC640-FDK includes the engineering documentation, ucf-files with all necessary pin assignments and basic timing constraints, and a well documented VHDL example application. This example application is called TPLD002 (Tews Programmable Logic Design) and covers the main functionalities of the TAMC640 like DMA capable PCIe endpoint with interrupt support, register mapping, DDR2 and QDR-II memory access and basic I/O to the FMC slot. It comes as a Xilinx ISE project with source code and as a ready-to-download bitstream. It is the basis for fast and reliable customer application development, and can significantly reduce time to market.

Software support for the TPLD002 is available for all major operating systems.


In-circuit programming and debugging of the FPGA design (e.g. using Xilinx "ChipScope") is supported. The Program and Debug Box TA900 allows access to the module while it is inserted in a system. It provides access to the module's JTAG Chain, the UART of the on-board Module Management Controller (MMC) and to two user pins of the Virtex-5 FPGA. If a UART core is implemented in the FPGA, serial communication via the TA900 is possible.

The TA900 can be accessed by USB 2.0 and by a 14-pin JTAG Header (e.g. for connecting a Xilinx Platform Cable).

For First-Time-Buyers the TA900 and the TAMC640-ED or TAMC640-FDK is recommended.

Technical Information

- Form Factor: PICMG AMC.0 R2.0 Module
 - Board size: single Mid-Size or Full-Size AMC
- AMC port 0,1 and 4 – 11 connected to FPGA MGTs
 - on-board AC-coupling for Rx and Tx
 - port speed up to 3.2Gb/sec
- AMC port 12 – 15 & 17 connected to FPGA I/Os
 - on-board AC-coupling for Rx and Tx
 - port speed up to 1.0Gb/sec
- TCLKA – TCLKD support
- Virtex-5 FPGA with integrated PCIe Endpoint Block
 - XC5VLX50T or XC5VLX85T
 - XC5VSX50T
- 1x QDR-II SRAM bank, 1 M x18 (2 MB)
- 2 x DDR2 DRAM bank, 64 M x16 (128 MB) each
- IPMI V1.5 support
- Front panel LEDs:
 - Blue Hot Swap LED
 - Red FAIL LED (LED1)
 - Green USER / Power Good LED (LED2)
- VITA 57.1 FMC Slot (high pin count)
 - 160 single ended I/Os or 80 differential
 - x2 Multi-Gigabit Link to FMC
 - $V_{ADJ} = 1.2 - 3.3$ Volt
- Operating temperature 0°C to +70°C
- MTBF (MIL-HDBK217F/FN2 G_B 20°C) TAMC640: 306000 h



Order Information

RoHS Compliant

TAMC640-10R	Virtex-5 FPGA Module, Single Mid-Size, XC5VLX50T-1, 256 MB DDR3, 2 MB QDR-II, FMC Slot
TAMC640-11R	Virtex-5 FPGA Module, Single Full-Size, XC5VLX50T-1, 256 MB DDR3, 2 MB QDR-II, FMC Slot
TAMC640-12R	Virtex-5 FPGA Module, Single Mid-Size, XC5VLX85T-1, 256 MB DDR3, 2 MB QDR-II, FMC Slot
TAMC640-13R	Virtex-5 FPGA Module, Single Full-Size, XC5VLX85T-1, 256 MB DDR3, 2 MB QDR-II, FMC Slot
TAMC640-14R	Virtex-5 FPGA Module, Single Mid-Size, XC5VSX50T-1, 256 MB DDR3, 2 MB QDR-II, FMC Slot
TAMC640-15R	Virtex-5 FPGA Module, Single Full-Size, XC5VSX50T-1, 256 MB DDR3, 2 MB QDR-II, FMC Slot

Optional available on request:

- Operating temperature -40°C to +85°C
- Faster FPGA speed grades
- 512 MB DDR2 (2 banks 128 M x 16)
- 4 MB QDR-II (1 bank of 2 M x 18) or 8 MB QDR-II (1 bank of 4 MB x 18)

For the availability of non-RoHS compliant (lead solder) products please contact TEWS.

Documentation

TAMC640-DOC	User Manual
TAMC640-ED	Engineering Documentation for TAMC640, includes TAMC640-DOC, Data Sheets, Constraints Files
TAMC640-FDK	FPGA Development Kit for TAMC640, includes TPLD002 Example Design

Accessories

TA900-10R	Program and Debug Box, USB, JTAG, 20pin FPC connector, including USB A-USB B and FPC Flexcable
------------------	--

Software

TDRV015-SW-25	Integrity Software Support (for the example design TPLD002 of the TAMC640-FDK)
TDRV015-SW-42	VxWorks (Legacy and VxBus-Enabled) Software Support (for the example design TPLD002 of the TAMC640-FDK)
TDRV015-SW-65	Windows Software Support (for the example design TPLD002 of the TAMC640-FDK)
TDRV015-SW-72	LynxOS Software Support (for the example design TPLD002 of the TAMC640-FDK)
TDRV015-SW-82	Linux Software Support (for the example design TPLD002 of the TAMC640-FDK)
TDRV015-SW-95	QNX Software Support (for the example design TPLD002 of the TAMC640-FDK)

For other operating systems please contact TEWS.