

TIP865

4 Channel Serial IP

Version 1.0

User Manual

Issue 1.0.12

June 2018

TEWS TECHNOLOGIES GmbH

Am Bahnhof 7 25469 Halstenbek, Germany

Phone: +49 (0) 4101 4058 0 Fax: +49 (0) 4101 4058 19

e-mail: info@tews.com www.tews.com

TIP865-10R

4 channel RS232 serial I/O

TIP865-11R

4 channel TTL serial I/O

TIP865-20R

4 channel RS422 serial I/O

This document contains information, which is proprietary to TEWS TECHNOLOGIES GmbH. Any reproduction without written permission is forbidden.

TEWS TECHNOLOGIES GmbH has made any effort to ensure that this manual is accurate and complete. However TEWS TECHNOLOGIES GmbH reserves the right to change the product described in this document at any time without notice.

TEWS TECHNOLOGIES GmbH is not liable for any damage arising out of the application or use of the device described herein.

Style Conventions

Hexadecimal characters are specified with prefix 0x, i.e. 0x029E (that means hexadecimal value 029E).

For signals on hardware products, an ‚Active Low‘ is represented by the signal name with # following, i.e. IP_RESET#.

Access terms are described as:

W	Write Only
R	Read Only
R/W	Read/Write
R/C	Read/Clear
R/S	Read/Set

©2018 by TEWS TECHNOLOGIES GmbH

All trademarks mentioned are property of their respective owners.

Issue	Description	Date
1.0	First Issue	June 1994
1.1	TIP865-30 added	September 1994
1.2	TIP865-51 added	October 2000
1.3	Add Interrupt Routing Description	August 2002
1.4	Addition "Technical Specification"	April 2003
1.5	Correction Baud Rate Value of TIP865-30	July 2003
1.6	Addition Maximum Baud Rates	September 2004
1.7	New address TEWS LLC	September 2006
1.0.8	Fixed a bug in Figure 6-1 and Updated Figures 1-1, 6-4 up to 6-6	December 2008
1.0.9	Addition "Technical Specification"	March 2009
1.0.10	Structural Document Revise	August 2010
1.0.11	General Revision	August 2014
1.0.13	Variants -30R and -51R have been removed from the manual due to EOL status of these variants.	June 2018

Table of Contents

1	PRODUCT DESCRIPTION	6
2	TECHNICAL SPECIFICATION	7
3	ID PROM CONTENTS.....	9
4	IP ADDRESSING	10
4.1	I/O Addressing.....	10
4.2	Memory Addressing.....	10
4.3	Interrupt Routing.....	10
5	PROGRAMMING HINTS.....	11
5.1	Using internal baud rates.....	11
5.2	Using external clock.....	11
5.2.1	Receiving an external clock.....	11
5.2.2	Transmitting an external clock signal.....	12
5.2.3	Overview clock I/O.....	12
5.3	Baud Rate Configuration.....	13
5.3.1	Clock selection.....	13
5.3.2	Maximum Baud Rate.....	13
6	INSTALLATION	14
6.1	TIP865-10R/-11R and TIP865-20R.....	14
6.1.1	DSR / DCD Jumper Configuration.....	14
6.1.2	External Clock Jumper Configuration.....	14
6.1.3	Jumper Location.....	15
6.1.4	Termination.....	15
7	PIN ASSIGNMENT – I/O CONNECTOR.....	16
7.1	50 Pin I/O Connector.....	16
7.2	DB9 I/O Pin Assignment.....	17
7.2.1	DB9 Pin Assignment: TIP865-10R RS232 and TIP865-11R TTL.....	17
7.2.2	DB9 Pin Assignment TIP865-20R RS422.....	18

List of Figures

FIGURE 1-1 : BLOCK DIAGRAM.....	6
FIGURE 6-1 : JUMPER LOCATION TIP865-10R/-11R/-20R	15
FIGURE 6-2 : TERMINATION TIP865-20R	15
FIGURE 7-1 : IP CONNECTOR ORIENTATION	19

List of Tables

TABLE 2-1 : TECHNICAL SPECIFICATION.....	8
TABLE 3-1 : ID PROM CONTENTS.....	9
TABLE 4-1 : REGISTER MAP.....	10
TABLE 4-2 : INTERRUPT ROUTING.....	10
TABLE 5-1 : EXTERNAL CLOCK SOURCE	12
TABLE 5-2 : MAXIMUM BAUD RATE.....	13
TABLE 6-1 : DSR/DCD JUMPER TABLE	14
TABLE 6-2 : EXTERNAL CLOCK JUMPER TABLE	14
TABLE 7-1 : PIN ASSIGNMENT I/O CONNECTOR.....	17
TABLE 7-2 : DB9 PIN ASSIGNMENT (TIP865-10R RS232 AND TIP865-11R TTL)	17
TABLE 7-3 : DB9 PIN ASSIGNMENT (TIP865-20R RS422)	18

1 Product Description

The TIP865 provides four channels of a high performance multi-mode serial interface. Five different versions are available. The TIP865-10R offers four RS232 interfaces, the TIP865-11R provides four TTL interfaces and the TIP865-20R supports four RS422 interfaces.

Full modem control is available for each of the 4 serial interfaces on the TIP865-10R and -11R supporting Rx/D, Tx/D, RTS, CTS, DCD and clock. The TIP865-20R provides Rx/D, Tx/D and clock.

Features include programmable baud rates to 2 Mbit/sec, asynchronous or synchronous protocols including NRZ, NRZI, FM, T1, SDLC/HDLC.

The communication controller used is the industry standard Z85C30.




Figure 1-1 : Block Diagram

2 Technical Specification

IP Interface	
Interface	Single Size IndustryPack® Logic Interface compliant to ANSI/VITA 4-1995
ID ROM Data	Format I Access: no wait states
I/O Space	Access: 1 wait state
Memory Space	Not used
Interrupts	Vectored interrupts, IntReq0 and IntReq1 used Access: 2 wait states
DMA	Not supported
Clock Rate	8 MHz
Module Type	Type I
On Board Devices	
Serial Communication Controller	Zilog Z85C3016PSC
I/O Interface	
Interface Connector	50-conductor flat cable
Termination	TIP865-10R:no termination TIP865-11R:no termination TIP865-20R:supports receive and transmit termination
I/O Signals	TIP865-10R (RS232): TxD, RTS, DTR, RxD, CTS, DSR, DCD, clock (in and out) TIP865-11R (TTL): TxD, RTS, DTR, RxD, CTS, DSR, DCD, clock (in and out) TIP865-20R (RS422): TxD, RxD, CLKIN, CLKOUT
Power Requirements	120mA typical @ +5V DC (measured with I/O pins open)
Physical Data	

Temperature Range	Operating Storage	0 °C to +70 °C -40°C to +125°C
MTBF	TIP865-10R: 1427000h TIP865-11R: 1518000h TIP865-20R: 1475000h MTBF values shown are based on calculation according to MIL-HDBK-217F and MIL-HDBK-217F Notice 2; Environment: G _B 2θ °C. The MTBF calculation is based on component FIT rates provided by the component suppliers. If FIT rates are not available, MIL-HDBK-217F and MIL-HDBK-217F Notice 2 formulas are used for FIT rate calculation.	
Humidity	5 – 95 % non-condensing	
Weight	TIP865-10R: 46g TIP865-11R: 42g TIP865-20R: 45g	

Table 2-1 : Technical Specification

3 ID Prom Contents

Address	Function	TIP865-10R	TIP865-11R	TIP865-20R
0x01	ASCII 'I'	0x49	0x49	0x49
0x03	ASCII 'P'	0x50	0x50	0x50
0x05	ASCII 'A'	0x41	0x41	0x41
0x07	ASCII 'C'	0x43	0x43	0x43
0x09	Manufacturer ID	0xB3	0xB3	0xB3
0x0B	Model Number	0x10	0x10	0x10
0x0D	Revision	0x10	0x10	0x10
0x0F	RESERVED	0x00	0x00	0x00
0x11	Driver-ID Low - Byte	0x00	0x00	0x00
0x13	Driver-ID High - Byte	0x00	0x00	0x00
0x15	Number of bytes used	0x10	0x10	0x10
0x17	CRC	0x21	0x9D	0x09
0x19	SIO1 : RS232	0x01		
0x1B	SIO2 : RS232	0x01		
0x1D	SIO3 : RS232	0x01		
0x1F	SIO4 : RS232	0x01		
0x19	SIO1 : TTL		0x02	
0x1B	SIO2 : TTL		0x02	
0x1D	SIO3 : TTL		0x02	
0x1F	SIO4 : TTL		0x02	
0x19	SIO1 : RS422			0x03
0x1B	SIO2 : RS422			0x03
0x1D	SIO3 : RS422			0x03
0x1F	SIO4 : RS422			0x03

Table 3-1 : ID PROM Contents

4 IP Addressing

4.1 I/O Addressing

The TIP865 is accessed in the I/O space through the following set of external registers of two Z85C30 Serial Communication Controllers (SCC).

Address	Name	Function	Size
0x01	CHCON2	Port 2 control register (SCC 1B Control)	byte
0x03	CHDAT2	Port 2 data register (SCC 1B Data)	byte
0x05	CHCON1	Port 1 control register (SCC 1A Control)	byte
0x07	CHDAT1	Port 1 data register (SCC 1A Data)	byte
0x09	CHCON4	Port 4 control register (SCC 2B Control)	byte
0x0B	CHDAT4	Port 4 data register (SCC 2B Data)	byte
0x0D	CHCON3	Port 3 control register (SCC 2A Control)	byte
0x0F	CHDAT3	Port 3 data register (SCC 2A Data)	byte

Table 4-1 : Register Map

4.2 Memory Addressing

Not used.

4.3 Interrupt Routing

The four serial communication ports of the TIP865 are realized with two Z85C30 Serial Communication Controllers. Each controller has its own Interrupt Request line which is routed direct to one of the IP interface signals INTREQ0 or INTREQ1.

Serial Communication Ports	IP Interrupt
Channel 1	INTREQ0
Channel 2	INTREQ0
Channel 3	INTREQ1
Channel 4	INTREQ1

Table 4-2 : Interrupt Routing

To enable interrupts for all four serial communication ports both serial communication controllers must be interrupt enabled. Also both interrupt request lines from the IP interface must be configured.

5 Programming Hints

Baud rates may be derived from a local 3.6864 MHz oscillator frequency is permitting the generation of all standard baud rates (including 19200, 38400 and 57600 baud) with zero error. Some networks and communication protocols may require a different oscillator frequency. For these applications the oscillator may be replaced or an external clock signal can be used.

Each channel of the Z85C30 SCC can be accessed by two addresses in the IP's I/O address space. However the Z85C30 SCC uses an internal set of fifteen registers for each channel, which can only be accessed indirectly. Please refer to the Z85C30 Data Sheet for writing own drivers. This data sheet is available from Zilog Corporation.

5.1 Using internal baud rates

The local 3.6864 MHz oscillator is connected with the RTxC# pin of all channels of the Z85C30 SCC. This is the standard configuration of feeding the programmable baud rate generator with an input clock. To enable the baud rate generator with the 3.6864 MHz clock, the driver software must set the bits D1, D0 of the SCC's internal register W14 to '01'.

To use the output of the baud rate generator as Transmit Clock and Receive Clock the bits D4, D3 and D6, D5 of the internal register WR11 must be set to '10'.

5.2 Using external clock

The TIP865 can be programmed to receive an external clock signal or to transmit an external clock signal. For both modes the SCC's pin TRxC# pin is used as I/O. It can be programmed to function as clock input or clock output.

Although the TRxC# pin of the Z85C30 SCC can be software configured to function as clock input or as clock output, the TIP865 hardware must be configured by jumpers in the corresponding mode.

Each individual channel can be configured by hardware and software to be the source of an external clock signal or to receive an external clock signal, but not both at the same time.

5.2.1 Receiving an external clock

To use the Z85C30 SCC's TRxC# pin as input for the external clock the bit D2 of internal register WR11 must be set to value '0'. The external clock is used as Transmit Clock if the bits D4, D3 of internal register WR11 are set to '01' and it is used as Receive Clock if the bits D6, D5 are set to '01'.

5.2.2 Transmitting an external clock signal

To use the Z85C30 SCC's TRxC# pin as output for the external clock the bit D2 of internal register WR11 must be set to value '1'. The source of the external clock signal is selected by the state of bits D1, D0 of the internal register WR11.

D1,D0	Clock Source
'00'	3.6864 MHz Oscillator
'01'	Transmit Clock
'10'	Baud Rate Generator Output
'11'	DPPL Output

Table 5-1 : External Clock Source

5.2.3 Overview clock I/O

The different TIP865 interfaces do not make all the same clock I/O functions available.

TTL – interface:

- Direct clock I/O – programmable via SCC register

RS232 – interface:

- Clock I/O direction selectable by jumper for each channel

RS422 – interface:

- Clock I/O direction selectable by jumper for each channel

5.3 Baud Rate Configuration

5.3.1 Clock selection

The on board Z85C30 SCC's provides four different clock sources for internal and external use. To select the source an internal write register of the Z85C30 must be used. Different clock sources for receiver and transmitter could be determined. Alternatively the RTxC# pin, the TRxC# pin, the Baud Rate generator output or the DPLL output could be selected.

- All TIP865 use the on board 3.6864MHz quartz oscillator for RTxC# Clock Input. This means for the TIP865-11R und -20R a maximum baud rate of 921.6kbit/sec. The RS232 transceiver of the TIP865-10R limits the baud rate of this interface to 57.6kbit/sec.
- The PCLK pin of the Z85C30 is routed to the 8 MHz IP clock or to the second on board 16 MHz quartz oscillator. The TIP865-10R, -11R and -20R are using the 8 MHz.
- Like description in chapter 5.2 the TRxC# pin of the Z85C30 could be used as clock input or clock output. If this pin is used for clock input, synchronous baud rates up to 2 Mbit are possible.

Additional to select the clock source TRxC# by programming the internal register of the Z85C30 the jumper configuration of TIP865-10R, -11R and -20R must be adjusted. For more information about external clock jumper location see chapter "External Clock Jumper Configuration" and "Clock Jumper Configuration".

5.3.2 Maximum Baud Rate

The maximum baud rate of the TIP865 is affected by several options like the clock input source, clock frequency, used clock mode, synchronous or asynchronous serial mode and the on board physical transceiver.

TIP865	Maximum Baud Rate		
	RTxC# Input	PCLK Input	Ext. Clock (TRxC#) Input
TIP865-10R RS232	57.6 kbit/sec	100 kbit/sec	100 kbit/sec
TIP865-11R TTL	921.6 kbit/sec	2 Mbit/sec	2 Mbit/sec
TIP865-20R RS422	921.6 kbit/sec	2 Mbit/sec	2 Mbit/sec

Table 5-2 : Maximum Baud Rate

6 Installation

6.1 TIP865-10R/-11R and TIP865-20R

6.1.1 DSR / DCD Jumper Configuration

The IBM PC compatible DB9 pin layout defines two separate pin for the signals DSR and DCD. However there is only one input at the Z85C30 SCC for this functionality. At the TIP865-10R RS232 IP and the TIP865-11R TTL IP the DSR or DCD can be individually selected for each channel by jumper.

Channel	DSR (jumper installed)	DCD (jumper installed)
1	J32 1—2	J32 2—3
2	J22 1—2	J22 2—3
3	J12 1—2	J12 2—3
4	J42 1—2	J42 2—3

Table 6-1 : DSR/DCD Jumper Table

The TIP865-20R RS422 IP does not provide DSR and DCD. For this version these jumpers are obsolete.

6.1.2 External Clock Jumper Configuration

The TIP865 provides an external clock signal for each channel, which can be programmed individually as external clock output or external clock input. This clock signal is controlled by corresponding TRxCB# pin of the Z85C30 SCC.

At the TIP865-10R RS232 IP and the TIP865-20R RS422 IP the external clock signal must be configured by jumper for input or output.

Channel	Clock out	Clock in
1	J11 close; J10 open	J11 open; J10 close
2	J21 close; J20 open	J21 open; J20 close
3	J31 close; J30 open	J31 open; J30 close
4	J41 close; J40 open	J41 open; J40 close

Table 6-2 : External Clock Jumper Table

The TIP865-11R TTL IP feeds the TRxCB# signal of the Z85C30 SCC directly to the clock I/O pin. For this version these jumpers are obsolete, because the clock signal can be software configured to be a clock input or clock output.

6.1.3 Jumper Location




Figure 6-1 : Jumper Location TIP865-10R/-11R/-20R

6.1.4 Termination

The TIP865-10R/-11R does not need a termination.

The TIP865-20R RS422 IP supports a standard RS422 termination with termination resistors. Both, receive and transmit termination are available separately for all four serial RS422 channels. A network within all 4 resistors is used to realize the termination. In order to deactivate the termination, the networks must be removed.

Channel	Receive Termination	Transmit Termination
1 + 2	N2 inserted	N1 inserted
3 + 4	N4 inserted	N3 inserted




Figure 6-2 : Termination TIP865-20R

7 Pin Assignment – I/O Connector

7.1 50 Pin I/O Connector

PIN	TIP865-10R/-11R	TIP865-20R
1	DCD 2	TxD+ 2
2	DSR 2	TxD- 2
3	RxD 2	CLKOUT+ 2
4	RTS 2	CLKOUT- 2
5	TxD 2	CLKIN+ 2
6	CTS 2	CLKIN- 2
7	DTR 2	RxD+ 2
8	clock 2	RxD- 2
9	GND	GND
10	DCD 1	TxD+ 1
11	DSR 1	TxD- 1
12	RxD 1	CLKOUT+ 1
13	RTS 1	CLKOUT- 1
14	TxD 1	CLKIN+ 1
15	CTS 1	CLKIN- 1
16	DTR 1	RxD+ 1
17	clock 1	RxD- 1
18	GND	GND
19	DCD 4	TxD+ 4
20	DSR 4	TxD- 4
21	RxD 4	CLKOUT+ 4
22	RTS 4	CLKOUT- 4
23	TxD 4	CLKIN+ 4
24	CTS 4	CLKIN- 4
25	DTR 4	RxD+ 4
26	clock 4	RxD- 4
27	GND	GND
28	DCD 3	TxD+ 3
29	DSR 3	TxD- 3
30	RxD 3	CLKOUT+ 3
31	RTS 3	CLKOUT- 3
32	TxD 3	CLKIN+ 3
33	CTS 3	CLKIN- 3
34	DTR 3	RxD+ 3
35	clock 3	RxD- 3
36	GND	GND
37		
38		

PIN	TIP865-10R/-11R	TIP865-20R
39		
40		
41		
42		
43		
44	GND	GND
45		
46	GND	GND
47		
48	GND	GND
49	+5V	+5V
50	GND	GND

Table 7-1 : Pin Assignment I/O Connector

7.2 DB9 I/O Pin Assignment

The 50 pin flat cable from the IP carrier board may be split into four 9 pin sections, each of these are mass terminated into standard DB9 D-shell connector. For TIP865-10R RS232 module the pin layout is identical with the IBM PC 9 pin connector layout. The only difference is, that pin 9 is not RI signal but used for external clock.

7.2.1 DB9 Pin Assignment: TIP865-10R RS232 and TIP865-11R TTL

PIN	Signal
1	DCD
2	RxD
3	TxD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	clock

Table 7-2 : DB9 Pin Assignment (TIP865-10R RS232 and TIP865-11R TTL)

7.2.2 DB9 Pin Assignment TIP865-20R RS422

PIN	Signal
1	TxD+
2	CLKOUT+
3	CLKIN+
4	RxD+
5	GND
6	TxD-
7	CLKOUT-
8	CLKIN-
9	RxD-

Table 7-3 : DB9 Pin Assignment (TIP865-20R RS422)




Figure 7-1 : IP Connector Orientation